3FIRECHIEF®

making the world a safer place

FIRECHIEF® CTX 2L SPRAY **FOAM EXTINGUISHER**

This Firechief® CTX Foam Extinguisher is an excellent solution for multi-risk usage. Ideal for use on A class fires (wood/paper) and B class (petrol & volatile liquids), the foam forms a flame smothering seal to prevent reignition.



- Kitemark certified to BS EN 3
- 5 year guarantee
- 35kV dielectric test
- Squeeze grip operation
- Internal polyethylene lining
- Spray nozzle
- Corrosion resistant finish
- Complete with bracket

Specifications

Model	CXF2
Product Code	100-1674
Description	Firechief® CTX 2L Foam Extinguisher
Capacity (I)	2
ire Rating 5A 55B	
Discharge Time (secs)	20
Working Pressure (bar)	15
Temperature Range (°C)	+5 to +60
Product Height (mm)	370
Product Diameter (mm)	110
Filled Weight (kg)*	3.6
Carton Height (mm)	400
Carton Length (mm)	100
Carton Width (mm)	100
Packaged Weight (kg)**	4
Product EAN	5055377963934









KM 95424 BS EN 3





Imported into EU by: Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Road, Dublin 4, D04 C2N4, Ireland

For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, LE15 6RB, UK | UK: 0330 999 0019 | International: +44 (0)1572 772657 | www.firechiefglobal.com/contact-us/







A B

^{*} Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging. ** Includes all packaging, hose / horn and bracket.



FIRECHIEF® CTX **SPRAY FOAM EXTINGUISHERS**



making the world a safer place

MODEL:

- Kitemark certified to BS EN 3
- 5 year guarantee
- Both sizes carry 75F fire rating
- 35kV dielectric test
- Squeeze grip operation
- Internal polyethylene lining
- Spray Nozzle
- Corrosion resistant finish



100-1610























FIRECHIEF® CTX SPRAY **FOAM EXTINGUISHERS**



The Firechief® CTX Foam Extinguishers are an excellent solution for multi-risk usage. Ideal for use on A class fires (wood/paper), B class (petrol & volatile liquids), and F class (cooking oil), the foam forms a flame smothering seal to prevent reignition.

MODEL:









Specifications

Model	CXF6	CXF9
Product Code	100-1610	100-1611
Description	Firechief® CTX 6L Foam Extinguisher	Firechief® CTX 9L Foam Extinguisher
Capacity (I)	6	9
Fire Rating	21A 144B 75F	21A 183B 75F
Discharge Time (secs)	≥15s	≥15s
Working Pressure (bar)	12	12
Temperature Range (°C)	+5 to +60	+5 to +60
Product Height (mm)	535	600
Product Diameter (mm)	162	184
Filled Weight (kg)*	9.3	13.7
Carton Height (mm)	570	620
Carton Length (mm)	175	195
Carton Width (mm)	170	190
Packaged Weight (kg)**	10	14.5
Product EAN	5055377962821	5055377962838

^{*} Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

Imported into EU by: Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Road, Dublin 4, D04 C2N4, Ireland

For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, LE15 6RB, UK | UK: 0330 999 0019 | International: +44 (0)1572 772657 | www.firechiefglobal.com/contact-us/







^{**} Includes all packaging, hose / horn and bracket.