





Orthomat® Premium

Reduces standing fatigue for those that move at work



- *Exceptional fatigue-relief properties – a real investment for the workplace.*
- *Dual layer construction for superior comfort and durability.*
- *Tough textured top surface for excellent resilience against wear and tear.*
- *Insulates against the effects of cold concrete floors.*
- *Low density underlayer provides extremely effective underfoot cushioning.*
- *Tapered edges to reduce trip hazards.*
- *Range of colours available.*
- *Ideal for demanding environments where regular turning is involved.*
- *Fire tested to BS EN 13501-1.*



Styles Available

Green

Blue

Black

Black / Yellow - NEW!

Parts

Part Number	Size	Colour	Weight (kg)
<i>FF010703C</i>	<i>0.9 m x per linear metre</i>	<i>Black/Yellow</i>	<i>1.35</i>
<i>FF010703</i>	<i>0.9 m x 18.3 m</i>	<i>Black/Yellow</i>	<i>24.71</i>
<i>FF010702</i>	<i>0.9 m x 1.5 m</i>	<i>Black/Yellow</i>	<i>2.03</i>
<i>FF010701</i>	<i>0.6 m x 0.9 m</i>	<i>Black/Yellow</i>	<i>0.81</i>
<i>FF040005</i>	<i>1.2 m x 18.3 m</i>	<i>Green</i>	<i>88</i>
<i>FF040003C</i>	<i>0.9 m x per linear metre</i>	<i>Green</i>	<i>3.8</i>
<i>FF040003</i>	<i>0.9 m x 18.3 m</i>	<i>Green</i>	<i>61</i>
<i>FF020003C</i>	<i>0.9 m x per linear metre</i>	<i>Blue</i>	<i>3.8</i>
<i>FF020003</i>	<i>0.9 m x 18.3 m</i>	<i>Blue</i>	<i>61</i>
<i>FF010006C</i>	<i>1.2 m x per linear metre</i>	<i>Black</i>	<i>5.1</i>
<i>FF010006</i>	<i>1.2 m x 18.3 m</i>	<i>Black</i>	<i>93.5</i>
<i>FF010005C</i>	<i>0.6 m x per linear metre</i>	<i>Black</i>	<i>2.49</i>
<i>FF010005</i>	<i>0.6 m x 18.3 m</i>	<i>Black</i>	<i>45.6</i>
<i>FF010004</i>	<i>0.9 m x 3.65 m</i>	<i>Black</i>	<i>12.15</i>
<i>FF010003C</i>	<i>0.9 m x per linear metre</i>	<i>Black</i>	<i>3.8</i>
<i>FF010003</i>	<i>0.9 m x 18.3 m</i>	<i>Black</i>	<i>61</i>
<i>FF010002</i>	<i>0.9 m x 1.5 m</i>	<i>Black</i>	<i>4.99</i>
<i>FF010001</i>	<i>0.6 m x 0.9 m</i>	<i>Black</i>	<i>2</i>

Technical Specifications

Material	<i>Open Cell PVC (Foam)</i>
Surface Finish	<i>Tough Textured top surface</i>
Product Height	<i>12.5 mm</i>
Roll Length	<i>18.3 m</i>
Min. Operating Temperature	<i>0°C</i>
Max. Operating Temperature	<i>+60°C</i>
Resistance to Chemicals	<i>Resistant to most chemicals</i>
Environmental Resistance	<i>Suitable for dry indoor environments</i>
Typical Applications	<i>Production lines, Assembly areas, Packing stations, Workbenches, Retail counters</i>
Installation Method	<i>Loose lay</i>
Cleaning Method	<i>Brush/mop the top surface</i>
Fire Tested to	<i>BS EN 13501-1 Class Dfl - s1</i>
Guarantee	<i>2 years when used in a dry environment</i>

Additional Information



Orthomat Premium Fire Test BS EN 13501



Orthomat Premium Fire Test EN ISO 9239



Orthomat Premium Fire Test EN ISO 11925

