



## Rampmat

*A popular honeycomb mat for all environments*



- *A popular choice of doormat, suitable for most climates.*
- *The raised honeycomb design provides grip while scraping away dirt and moisture.*
- *Moulded bevelled edging for trip-resistance and wheeled access.*
- *Manufactured from durable rubber.*
- *Slip tested to DIN 51130.*



## Parts

Part Number	Size	Colour	Weight (kg)
RP010002	0.8 m x 1.2 m	Black	5
RP010001	0.9 m x 1.5 m	Black	8

## Technical Specifications

Material	Rubber mix, including >50% recycled material
Recycled Material Content %	70%
Surface Finish	Raised circular surface
Product Height	12 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+130°C
Environmental Resistance	Suitable for wet and dry environments, indoors or outdoors

Typical Applications	General industrial, Areas where swarf is prevalent.
Installation Method	<i>Loose lay</i>
Cleaning Method	<i>Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt</i>
Tensile Strength	<i>2.75 to 3.25 MPa</i>
Notes	<i>Silicone is used in the production process of the mats and a residue will possibly be left on the mat</i>
Slip Tested to	<i>DIN 51130 - R10</i>

## Additional Information



**Rampmat Ramp Slip Test DIN 51130**