

LogoScrape LogoScrape

LogoScrape delivers superior scraping action to effectively remove dirt and debris, making it a practical solution for both indoor and outdoor environments. It is available with two backing options: solid rubber for indoor use and a version with integrated drainage holes for outdoor applications, allowing water to self-drain and helping to maintain a safer, drier surface.

Built for durability, LogoScrape features a compression-moulded rubber backing with reinforced borders on all four sides, ensuring long-lasting performance even in high-traffic areas.

The surface is made from 100% ECONYL® regenerated nylon derived from waste products, and the rubber backing contains 34% post-industrial recycled content, combining strength with sustainability.


Logo mats are the perfect platform to showcase your company logo or message. With LogoScrape, you have a customisable solution that works for both indoor and outdoor use. Choose from over 50 colours to create a design that reflects your brand. We offer a range of sizes, but bespoke dimensions are also available to suit your specific needs.

To order, decide on your mat size and whether it's for indoor or outdoor use, email a high-resolution image of your design and brand guidelines to sales@bluediamond.uk.com in PDF, JPEG, or similar file format. Once your order is confirmed, you'll receive a full-colour proof for approval.

Please note: The maximum size for LogoScrape for outdoor (with drainage holes) is 130cm x 200cm and indoor (no drainage holes) is 200cm x 600cm. The size of the holes are 7mm in diameter.

Features

- ▼ Typical applications: Perfect for indoor and outdoor use in schools, universities, public buildings, sports facilities, shopping malls, offices, hotels and bars, and restaurants.
- Material: 100% ECONYL® regenerated nylon surface derived from waste products, with 100% nitrile backing containing 34% post-industrial recycled content.
- Cleaning: Use a vacuum cleaner or an extraction cleaner to remove dirt. LogoScrape is also machine washable.





For more information about this product or, to place an order click here



LogoScrape LogoScrape

Code	Metric	Imperial	Thickness	Weight	Туре	
LS2436	60cm x 85cm	2' x 3'	10mm	1.99kg	Indoor	
LS3648	85cm x 115cm	3' x 4'	10mm	3.8kg	Indoor	
LS3660	85cm x 150cm	3' x 5'	10mm	5.08kg	Indoor	
LS310	85cm x 300cm	3' x 10'	10mm	9.9kg	Indoor	
LS4872	115cm x 180cm	4' x 6'	10mm	8.07kg	Indoor	
LS4879	115cm x 200cm	4' x 7'	10mm	8.97kg	Indoor	
LS4896	115cm x 240cm	4' x 8'	10mm	10.8kg	Indoor	
LS5979	150cm x 200cm	5' x 7'	10mm	11.7kg	Indoor	
LS5998	150cm x 250cm	5' x 8'	10mm	14 .63kg	Indoor	
LS5910	150cm x 300cm	5' x 10'	10mm	17.6kg	Indoor	
LS7910	200cm x 300cm	7' x 10'	10mm	23.4kg	Indoor	
LSO2436	60cm x 85cm	2' x 3'	10mm	1.99kg	Outdoor	
LSO3648	85cm x 115cm	3' x 4'	10mm	3.8kg	Outdoor	
LSO3660	85cm x 150cm	3' x 5'	10mm	5.08kg	Outdoor	
LSO4872	115cm x 180cm	4' x 6'	10mm	8.07kg	Outdoor	
LSO4879	115cm x 200cm	4' x 7'	10mm	8.97kg	Outdoor	

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number Please note, the maximum size for LogoScrape for outdoor (with drainage holes) is $130 \, \text{cm} \times 200 \, \text{cm}$ and indoor (no drainage holes) is $200 \, \text{cm} \times 200 \, \text{cm}$

Technical Specification				
Slip resistant:	Great slip resistance to level 2			
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall			
Water absorbent:	3.160kg/m² absorbancy. When used externally, drainage holes allow water to self-drain			
Crush resistant:	Great crush resistance to level 2			
Soil resistant:	Excellent resistance to soiling and stains to level 3			
Chemical resistant:	Yes, maximum oil resistance			





Technical Specification					
Cut to length:	Bespoke sizes available on request				
Cut to size:	Bespoke sizes available on request				
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users				
Dry area:	Yes				
Wet area:	Yes				
Heavy area:	Yes				
Environment:	Suitable for indoor and outdoor use				
Flame retardant:	Yes				
Product testing:	 Static Electrical Propensity – Walking Test: 0.3 kV (ISO 6356) Dynamic Coefficient of Friction: 0.50 DS (EN 13893) Flammability: Classified Dfl-s1 (EN 13501-1) 				
Sustainability:	 Surface is made from 100% ECONYL® regenerated nylon derived from waste products 100% nitrile backing contains 34% post-industrial recycled content 				
Cleaning:	Use a vacuum cleaner or an extraction cleaner. LogoScrape is also machine washable				
Machine washable:	Maximum 40-50°C - Mat can also be tumble dried. Due to its abrasive pile, LogoScrape may attract lint if washed with other mat type: For best results, wash separately. If mixed washing is unavoidable, tumble-dry to reduce linting. After drying, lay mats flat to cool before rolling. Avoid storing damp mats folded or stacked to prevent colour transfer				

ECONYL®

The ECONYL® regeneration process gives a new life to waste materials that would otherwise be sent to landfill, transforming them into a new source of opportunities, in this case LogoScrape.

Nylon waste – such as fishing nets, fabric scraps, carpet flooring, and industrial plastic – is recovered and converted into new yarn, which has the same qualitative characteristics as traditional nylon.

In the Life Cycle assessment of the nylon value chain, they discovered that the highest negative impact on our planet came from the raw material extraction phase.

Years and years of research finally led to the development of the ECONYL® Regeneration System: a highly innovative industrial process that allows replacing caprolactam (the main component to produce Nylon 6, derived from oil) with alternative raw materials coming from the recycling of various types of nylon waste.



LogoScrape LogoScrape

Colour Chart

Al	B1	C1	Dì		El	
A2	B2	C2	D2		E2	
A3	В3	C3	D3		E3	
A4	B4	C4	D4		E4	
A5	B5	C5	D5		E5	
A6	B6	C6	D6		E6	
A7	В7	C7	D7	San	E7	
A8	B8	C8	D8		E8	
A9	B9	C9	D9		E9	
A10	B10	C10	D10		E10	