



## Parts

Part Number	Size	Colour	Weight (kg)
<b>BF010004</b>	<b>0.6 m x 0.9 m</b>	<b>Black</b>	<b>6.35</b>
<b>BF010003</b>	<b>0.6 m x 0.9 m</b>	<b>Black</b>	<b>6.35</b>
<b>BF010002</b>	<b>0.9 m x 1.2 m</b>	<b>Black</b>	<b>10.5</b>
<b>BF010001</b>	<b>0.6 m x 0.9 m</b>	<b>Black</b>	<b>6.35</b>

## Bubblemat

*Smart anti-fatigue mat with a distinctive bubbled surface*



- Raised bubble patterned surface stimulates feet and legs to aid circulation.
- Underfoot cushioning also makes prolonged occupational standing more comfortable.
- Complete mats suitable for workstations.

## Technical Specifications

Material	<i>Natural rubber</i>
Recycled Material Content %	43%
Natural Material Content %	57
Surface Finish	<i>Bubble</i>

Product Height	14 mm
Min. Operating Temperature	-30°C
Max. Operating Temperature	+50°C
Resistance To Chemicals	<i>Not resistant to fat and mineral oil</i>
Environmental Resistance	<i>Suitable for predominantly dry environments</i>
UV Resistance	Yes
Typical Applications	<i>General industrial</i>
Installation Method	<i>Loose lay interlocking mats</i>
Cleaning Method	<i>Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats</i>
Tensile Strength	3 MPa
Elongation	250%
Manufacturing Process	<i>Compression moulding</i>