


## COBAmat® Light

Standing the test of time, our original safety matting



- The original premium multi-purpose safety mat widely used across the industry today.
- An ideal choice for longer production lines, or for covering mezzanine floors.
- Available in four vibrant colours and four weave (hole) sizes to suit the application.
- Vinyl strips are interwoven, rather than welded, for better flexibility and lower risk of breaking.
- Cross-ribbed grip to reduce slipping.
- Fully reversible for added longevity.
- Suitable for use in wet and dry environments, or where swarf and debris cause problems.
- Fire tested to BS EN 13501-1 and slip tested to DIN 51130.
- Widely used in a range of industrial and non-industrial environments, both wet and dry.
- 30 mm x 30 mm hole size.



### Parts

Part Number	Size	Colour	Weight (kg)
CO041210	1.2 m x 10 m	Green	44
CO031210	1.2 m x 10 m	Red	44
CO021210	1.2 m x 10 m	Blue	44
CO011210	1.2 m x 10 m	Black	44
CO041205	1.2 m x 5 m	Green	22
CO031205	1.2 m x 5 m	Red	22
CO021205	1.2 m x 5 m	Blue	22
CO011205	1.2 m x 5 m	Black	22
CO040910	0.9 m x 10 m	Green	32
CO030910	0.9 m x 10 m	Red	32

### Technical Specifications

Material	PVC
Surface Finish	Cross ribbed lattice
Product Height	12 mm
Hole Size	30 mm x 30 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+60°C
Resistance to Chemicals	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and

Part Number	Size	Colour	Weight (kg)
CO020910	0.9 m x 10 m	Blue	32
CO010910	0.9 m x 10 m	Black	32
CO040905	0.9 m x 5 m	Green	16
CO030905	0.9 m x 5 m	Red	16
CO020905	0.9 m x 5 m	Blue	16
CO010905	0.9 m x 5 m	Black	16
CO040610	0.6 m x 10 m	Green	22
CO030610	0.6 m x 10 m	Red	22
CO020610	0.6 m x 10 m	Blue	22
CO010610	0.6 m x 10 m	Black	22
CO040605	0.6 m x 5 m	Green	11
CO030605	0.6 m x 5 m	Red	11
CO020605	0.6 m x 5 m	Blue	11
CO010605	0.6 m x 5 m	Black	11

*grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details*

Environmental Resistance	<i>Suitable for wet and dry environments, indoors or outdoors</i>
UV Resistance	<i>Resistant to UV, but please note that red is not colourfast in direct sunlight</i>
Typical Applications	<i>General industrial, Engineering, Machine tool areas where swarf prevalent</i>
Installation Method	<i>Loose lay, reversible</i>
Cleaning Method	<i>Pressure hose with mild detergent if required</i>
Slip Tested to	<i>DIN 51130 - R10</i>

## Additional Information



*Workstation Ramp Slip Test DIN 51130*



*Workstation Fire Test EN ISO 11925*



*Workstation Fire Test EN ISO 9239*



*Workstation Fire Test BS EN 13501*