



## COBAmat® Standard

*Standing the test of time, our original safety matting*



- The original premium multi-purpose safety mat widely used across the industry today.
- An ideal choice for longer production lines, or for covering mezzanine floors.
- Available in four vibrant colours and four weave (hole) sizes to suit the application.
- Vinyl strips are interwoven, rather than welded, for better flexibility and lower risk of breaking.
- Cross-ribbed grip to reduce slipping.
- Fully reversible for added longevity.
- Suitable for use in wet and dry environments, or where swarf and debris cause problems.
- Fire tested to BS EN 13501-1 and slip tested to DIN 51130.
- The largest hole size available in COBAmat, this matting is ideally suited to trapping swarf and larger debris particles.
- Commonly used in areas such as machine shops with lathes,
- assembly/finishing areas where offcuts and debris may be present.
- 22 mm x 22 mm hole size.

## Parts

Part Number	Size	Colour	Weight (kg)
CS040610C	0.6 m x per linear metre	Green	2.6
CS040910C	0.9 m x per linear metre	Green	5.1
CS041210C	1.2 m x per linear metre	Green	5.6
CS020910C	0.9 m x per linear metre	Blue	4
CS020610C	0.6 m x per linear metre	Blue	2.6
CS010910C	0.9 m x per linear metre	Black	4
CS010610C	0.6 m x per linear metre	Black	2.6
CS041210	1.2 m x 10 m	Green	56
CS031210	1.2 m x 10 m	Red	56
CS021210	1.2 m x 10 m	Blue	56

## Technical Specifications

Material	PVC
Surface Finish	Cross ribbed lattice
Product Height	12 mm
Hole Size	22 mm x 22 mm
Min.	
Operating Temperature	-20°C
Max.	
Operating Temperature	+60°C
Resistance to Chemicals	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and

Part Number	Size	Colour	Weight (kg)
CS011210	1.2 m x 10 m	Black	56
CS041205	1,2 m x 5 m	Green	28
CS031205	1,2 m x 5 m	Red	28
CS021205	1,2 m x 5 m	Blue	28
CS011205	1,2 m x 5 m	Black	28
CS040910	0.9 m x 10 m	Green	40
CS030910	0.9 m x 10 m	Red	40
CS020910	0.9 m x 10 m	Blue	40
CS010910	0.9 m x 10 m	Black	40
CS040905	0.9 m x 5 m	Green	20
CS030905	0.9 m x 5 m	Red	20
CS020905	0.9 m x 5 m	Blue	20
CS010905	0.9 m x 5 m	Black	20
CS040610	0.6 m x 10 m	Green	26
CS030610	0.6 m x 10 m	Red	26
CS020610	0.6 m x 10 m	Blue	26
CS010610	0.6 m x 10 m	Black	26
CS040605	0.6 m x 5 m	Green	13
CS030605	0.6 m x 5 m	Red	13
CS020605	0.6 m x 5 m	Blue	13
CS010605	0.6 m x 5 m	Black	13

grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details

UV Resistance	Suitable for wet and dry environments, indoors or outdoors
Typical Applications	Resistant to UV, but please note that red is not colourfast in direct sunlight
Typical Applications	Resistant to UV, but please note that red is not colourfast in direct sunlight
Installation Method	Loose lay, reversible
Cleaning Method	Pressure hose with mild detergent if required
Slip Tested To	DIN 51130 - R10

## Additional Information



Workstation Ramp Slip Test DIN 51130



Workstation Fire Test EN ISO 9239



Workstation Fire Test EN ISO 11925



Workstation Fire Test BS EN 13501