


## Fatigue-Step®

*Safety rubber tiles for playgrounds*



- *Interlocking rubber tile system to cover large or small areas.*
- *Provides safety for playgrounds. Anti-slip surface reduces risks (tested to DIN 51130). Ideal safety matting for outdoor areas.*
- *Durable and easy to clean.*
- *Easy to relocate or replace.*
- *Fits in natural environment.*
- *Suitable for all weather, extreme temperatures and resists wind uplift*
- *Open holes allow grass growth and provide optimal drainage.*



## Parts

Part Number	Size	Colour	Weight (kg)
SS010001	0.9 m x 0.9 m	Black	9.95

## Technical Specifications

Material	Rubber mix, including >50% recycled material
Surface Finish	Textured with holes to allow drainage
Product	18 mm
Height	18 mm
Hole Size	22 mm
Min. Operating Temperature	-20°C

Max. Operating Temperature	+130°C
Resistance to Chemicals	<i>Natural rubber offers limited resistance to chemicals and oils</i>
Environmental Resistance	<i>Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.</i>
UV Resistance	Yes
Typical Applications	<i>Childrens play areas</i>
Installation Method	<i>Loose lay interlocking tiles</i>
Cleaning Method	<i>Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt</i>
Storage and application	<i>Store at room temperature, free from deformations.</i>
Tensile Strength	<i>3 to 3.5 MPa</i>
Notes	<i>Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water.</i>
Slip Tested to	<i>DIN 51130 - R10</i>

## Additional Information



**Installation Guide**



**Fatigue Step DIN 51130 Ramp Slip Test**