



Fatigue-Step® Solid

Modular anti-fatigue matting for larger areas



- Tiles link together to provide a very comfortable anti-fatigue surface.
- Simple to press-together connectors for installation on-site.
- Compatible with Fatigue-Step Grit tiles.
- Individual tiles can be moved and replaced with ease.
- Manufactured with Natural rubber and 25% nitrile.
- Fully slip tested – see datasheet for details.
- Optional ramped edging in yellow or black.



Parts

Part Number	Size	Colour	Weight (kg)
ST010001	0.9 m x 0.9 m	Black	10.5

Technical Specifications

Material	Standard - Natural rubber with 25% NBR
Surface Finish	Solid textured
Product Height	18 mm
Min. Operating Temperature	-20°C
Max.	+130°C

Operating Temperature	
Resistance to Chemicals	<i>Limited resistance to chemicals and oils</i>
Environmental Resistance	<i>Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.</i>
UV Resistance	Yes
Typical Applications	<i>General industrial</i>
Installation Method	<i>Loose lay interlocking tiles</i>
Cleaning Method	<i>Use of hard detergents not recommended</i>
Storage and Application	<i>Store at room temperature, free from deformations.</i>
Tensile Strength	<i>3.5 to 4 MPa</i>
Notes	<i>Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water</i>
Slip Tested to	<i>DIN 51130 - R10</i>

Additional Information



Installation Guide



Solid Fatigue Step Ramp Slip Test DIN 51130