





Orthomat® Comfort Plus

Athicker, double layer foam anti-fatigue mat for maximum levels of comfort - now also with added yellow borders for extra visibility and security.



- A thicker, dual layer foam anti-fatigue mat for maximum levels of comfort.
- The new wear resistant top surface provides additional resilience against wear and tear.
- Insulates against cold concrete floors.
- Best suited to dry environments.
- Checker plate surface provides attractive appearance.
- Available in mats and rolls.
- Ideal for demanding environments where regular turning is involved.



Parts

Part Number	Size	Colour	Weight (kg)
OCP010703C	0.9 m x per linear metre	Black/Yellow	3.75
OCP010703	0.9 m x 18.3 m	Black/Yellow	68.6
OCP010702	0.9 m x 1.5 m	Black/Yellow	5.65
OCP010701	0.6 m x 0.9 m	Black/Yellow	2.25
OCP010006C	1.2 m x per linear metre	Black	5
OCP010006	1.2 m x 18.3 m	Black	91.5

Technical Specifications

Material	Open Cell PVC foam
Surface Finish	Tough Checker plate surface
Product Height	15 mm
Min. Operating Temperature	0°C
Max. Operating Temperature	+60°C
Suitable for dry indoor environments	

Part Number	Size	Colour	Weight (kg)
<i>OCP010003C</i>	<i>0.9 m x per linear metre</i>	<i>Black</i>	<i>3.75</i>
<i>OCP010003</i>	<i>0.9 m x 18.3 m</i>	<i>Black</i>	<i>68.6</i>
<i>OCP010002</i>	<i>0.9 m x 1.5 m</i>	<i>Black</i>	<i>5.65</i>
<i>OCP010001</i>	<i>0.6 m x 0.9 m</i>	<i>Black</i>	<i>2.25</i>

Resistance	
Typical Applications	<i>Production lines, Assembly areas, Packing stations, Workbenches</i>
Installation Method	<i>Loose lay</i>
Cleaning Method	<i>Brush/mop the top surface</i>
Fire Tested to	<i>BS EN 13501-1 Class Cfl - s1</i>
Guarantee	<i>2 year when used in a dry environment</i>

Additional Information



Orthomat Comfort Plus Fire Test BS EN 13501



Orthomat Comfort Plus Fire Test EN ISO 9239



Orthomat Comfort Plus Fire Test EN ISO 11925