


COBAmat® Heavy

Standing the test of time, our original safety matting



- The original premium multi-purpose safety mat widely used across the industry today.
- An ideal choice for longer production lines, or for covering mezzanine floors.
- Available in four vibrant colours and four weave (hole) sizes to suit the application.
- Vinyl strips are interwoven, rather than welded, for better flexibility and lower risk of breaking.
- Cross-ribbed grip to reduce slipping.
- Fully reversible for added longevity.
- Suitable for use in wet and dry environments, or where swarf and debris cause problems.
- Fire tested to BS EN 13501-1 and slip tested to DIN 51130.
- The toughest of all the COBAmat® options for enhanced durability.
- Extra strength is derived from the smaller hole size which makes it more rigid.
- Fixing blocks are available to secure the matting in place.
- 22 mm x 10 mm hole size.



Parts

| Part Number | Size | Colour | Weight (kg) |
|-------------|--------------------------|--------|-------------|
| CD010910C | 0.9 m x per linear metre | Black | 5.2 |
| CD020910C | 0.9 m x per linear metre | Blue | 5.2 |
| CD011210C | 1.2 m x per linear metre | Black | 7.2 |
| CD020610C | 0.6 m x per linear metre | Blue | 3.5 |
| CD040905 | 0.9 m x 5 m | Green | 26 |
| CD030905 | 0.9 m x 5 m | Red | 26 |
| CD020905 | 0.9 m x 5 m | Blue | 26 |
| CD010905 | 0.9 m x 5 m | Black | 26 |
| CD040610 | 0.6 m x 10 m | Green | 35 |
| CD030610 | 0.6 m x 10 m | Red | 35 |

Technical Specifications

| | |
|----------------------------|---|
| Material | PVC |
| Surface Finish | Cross ribbed lattice |
| Product Height | 12 mm |
| Hole Size | 22 mm x 10 mm |
| Min. Operating Temperature | -20°C |
| Max. Operating Temperature | +60°C |
| Resistance to Chemicals | PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and |

| Part Number | Size | Colour | Weight (kg) |
|-------------|--------------|--------|-------------|
| CD020610 | 0.6 m x 10 m | Blue | 35 |
| CD010610 | 0.6 m x 10 m | Black | 35 |
| CD040605 | 0.6 m x 5 m | Green | 17 |
| CD030605 | 0.6 m x 5 m | Red | 17 |
| CD020605 | 0.6 m x 5 m | Blue | 17 |
| CD010605 | 0.6 m x 5 m | Black | 17 |
| CD041210 | 1.2 m x 10 m | Green | 72 |
| CD031210 | 1.2 m x 10 m | Red | 72 |
| CD021210 | 1.2 m x 10 m | Blue | 72 |
| CD011210 | 1.2 m x 10 m | Black | 72 |
| CD041205 | 1.2 m x 5 m | Green | 36 |
| CD031205 | 1.2 m x 5 m | Red | 36 |
| CD021205 | 1.2 m x 5 m | Blue | 36 |
| CD011205 | 1.2 m x 5 m | Black | 36 |
| CD040910 | 0.9 m x 10 m | Green | 52 |
| CD030910 | 0.9 m x 10 m | Red | 52 |
| CD020910 | 0.9 m x 10 m | Blue | 52 |
| CD010910 | 0.9 m x 10 m | Black | 52 |

grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details

| | |
|--------------------------|---|
| Environmental Resistance | <i>Suitable for wet and dry environments, indoors or outdoors</i> |
| UV Resistance | <i>Resistant to UV, but please note that red is not colourfast in direct sunlight</i> |
| Typical Applications | <i>General industrial, Engineering, Machine tool areas</i> |
| Installation Method | <i>Loose lay, reversible</i> |
| Cleaning Method | <i>Pressure hose with mild detergent if required</i> |
| Slip Tested to | <i>DIN 51130 - R10</i> |

Additional Information



Workstation Fire Test BS EN 13501



Workstation Fire Test EN ISO 9239



Workstation Fire Test EN ISO 11925



Workstation Ramp Slip Test DIN 51130