



Orthomat® Premium Bubble

Our new Extraordinary anti-fatigue mat with a distinctive bubbled surface



- *Exceptional fatigue-relief and fatigue-prevention properties.*
- *Dual layer construction for superior comfort and durability.*
- *Raised bubble patterned surface stimulates feet and legs aids circulation and prevents fatigue.*
- *Tough top surface for excellent resilience against wear and tear.*
- *Low density under layer provides extremely effective underfoot cushioning and insulates against the effects of cold concrete floors.*
- *Raised bubble pattern also reduces slip risk.*
- *Ideal for demanding locations, especially where regular turning is involved.*
- *Tapered edges to reduce trip hazards.*
- *Available in a high visibility version with bright yellow borders.*
- *Ideal for lighter industrial use where the user doesn't turn regularly in a static position.*

Styles Available

Black/Yellow



Black

Parts

Part Number	Size	Colour	Weight (kg)
<i>OPB010003C</i>	<i>0.9 m x per linear metre</i>	<i>Black</i>	<i>3.9</i>
<i>OPB010703C</i>	<i>0.9 m x per linear metre</i>	<i>Black/Yellow</i>	<i>3.92</i>
<i>OPB010703</i>	<i>0.9 m x 18.3 m</i>	<i>Black/Yellow</i>	<i>71.72</i>
<i>OPB010702</i>	<i>0.9 m x 1.5 m</i>	<i>Black/Yellow</i>	<i>5.37</i>
<i>OPB010701</i>	<i>0.6 m x 0.9 m</i>	<i>Black/Yellow</i>	<i>2.15</i>
<i>OPB010003</i>	<i>0.9 m x 18.3 m</i>	<i>Black</i>	<i>71.72</i>
<i>OPB010002</i>	<i>0.9 m x 1.5 m</i>	<i>Black</i>	<i>5.37</i>
<i>OPB010001</i>	<i>0.6 m x 0.9 m</i>	<i>Black</i>	<i>2.15</i>

Technical Specifications

Material	<i>Open Cell PVC Foam</i>
Surface Finish	<i>Raised bubble pattern surface</i>
Product Height	<i>12.5mm base/ 16mm with bubble</i>
Product Weight	<i>3.98kg per square metre</i>
Min. Operating Temperature	<i>0°C</i>
Max. Operating Temperature	<i>+60°C</i>
Resistance to Chemical	<i>Resistant to most chemicals</i>
Environmental Resistance	<i>Suitable for dry indoor environments</i>
Typical Application	<i>Production lines, assembly areas, packaging stations, workbenches and retail counters</i>
Installation Method	<i>Loose lay</i>
Guarantee	<i>2 years when used in a dry environment</i>